

### Section 1. Product and company identification

<b>GHS product identifier</b>	Methyl Fluoride
<b>Chemical name</b>	fluoromethane
<b>Other means of identification</b>	Methane, fluoro-; HFC-41; methyl fluoride; METHYL FLUORIDE; HFC-41; Halocarbon 41
<b>Product type</b>	Gas
<b>Product use</b>	Synthetic/Analytical chemistry.
<b>Supplier's details</b>	Joinpath Materials Technology (Shanghai) Co., Ltd. Room 12252, Building 2, No. 1 Haikun Road, Fengxian District, Shanghai 021-32098022
<b>24-hour telephone</b>	021-32098022

### Section 2. Hazards identification

<b>OSHA/HCS status:</b>	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
<b>Classification of the substance or mixture:</b>	FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Compressed gas

#### GHS label elements

#### Hazard pictograms:



<b>Signal word:</b>	Danger
<b>Hazard statements:</b>	Extremely flammable gas. May form explosive mixtures with air. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.

#### Precautionary statements:

<b>General:</b>	Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Approach suspected leak area with caution.
<b>Prevention:</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>Response:</b>	Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.
<b>Storage:</b>	Protect from sunlight. Store in a well-ventilated place.
<b>Disposal:</b>	Not applicable.

**Hazards not otherwise classified:**

Liquid can cause burns similar to frostbite. May displace oxygen and cause rapid suffocation.

### Section 3. Composition/information on ingredients

Substance/mixture:	Substance	
Ingredient name	%	CAS number
Methyl Fluoride	100	593-53-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

##### Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

##### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

##### Skin contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

##### Ingestion

As this product is a gas, refer to the inhalation section.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

##### Eye contact

Contact with rapidly expanding gas may cause burns or frostbite.

##### Inhalation

No known significant effects or critical hazards.

##### Skin contact

Contact with rapidly expanding gas may cause burns or frostbite.

##### Frostbite

Try to warm up the frozen tissues and seek medical attention.

<b>Ingestion</b>	As this product is a gas, refer to the inhalation section.
<b>Over-exposure signs/symptoms</b>	
<b>Eye contact</b>	No specific data.
<b>Inhalation</b>	No specific data.
<b>Skin contact</b>	No specific data.
<b>Ingestion</b>	No specific data.
<b>Indication of immediate medical attention and special treatment needed, if necessary</b>	
<b>Notes to physician</b>	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
<b>Specific treatments</b>	No specific treatment.
<b>Protection of first-aiders</b>	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## Section 5. Fire-fighting measures

<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Use an extinguishing agent suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
<b>Hazardous thermal decomposition products</b>	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides
<b>Special protective actions for fire-fighters</b>	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.
<b>Special protective equipment for fire-fighters</b>	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency</b>	Accidental releases pose a serious fire or explosion hazard. No action shall

<b>personnel</b>	be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
<b>For emergency responders</b>	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".
<b>Environmental precautions</b>	Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
<b>Methods and materials for containment and cleaning up</b>	
<b>Small spill</b>	Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.
<b>Large spill</b>	Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Precautions for safe handling

<b>Protective measures</b>	Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement. Use only non-sparking tools. Avoid contact with eyes, skin and clothing. Empty containers retain product residue and can be hazardous. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment.
<b>Advice on general occupational hygiene</b>	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
<b>Conditions for safe storage, including any</b>	Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-

### incompatibilities

ventilated area, away from incompatible materials (see Section 10).  
Eliminate all ignition sources. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).  
Keep container tightly closed and sealed until ready for use. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Methyl Fluoride	ACGIH TLV (United States, 3/2017). TWA: 2.5 mg/m <sup>3</sup> , (as F) 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 2.5 mg/m <sup>3</sup> , (as F) 8 hours. OSHA PEL (United States, 6/2016). TWA: 2.5 mg/m <sup>3</sup> , (as F) 8 hours. OSHA PEL Z2 (United States, 2/2013). TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: Dust

### Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.  
Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

Safety eyewear complying with an approved standard should be used when

a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side- shields.

### Skin protection

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti- static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

### Appearance

### Physical state

Gas. [Liquefied gas]

### Color

Colorless.

### Odor

Sweet odor

### Odor threshold

Not available

### pH

Not applicable

### Melting point

-141.85°C (-223.3°F)

### Boiling point

-77.15°C (-106.9°F)

### Critical temperature

44.59°C (112.3°F)

### Flash point

Not available.

### Evaporation rate

Not available.

### Flammability (solid, gas)

Not available.

<b>Lower and upper explosive (flammable) limits</b>	Lower: 5.6%
<b>Vapor pressure</b>	525 (psia)
<b>Vapor density</b>	Not available.
<b>Specific Volume (ft 3/lb)</b>	11.1235
<b>Gas Density (lb/ft 3)</b>	0.0899
<b>Relative density</b>	Not applicable.
<b>Solubility</b>	Not available.
<b>Solubility in water</b>	Not available.
<b>Partition coefficient: n-octanol/water</b>	0.51
<b>Auto-ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available
<b>Flow time (ISO 2431)</b>	Not available
<b>Molecular weight</b>	34.03 g/mole

## Section 10. Stability and reactivity

<b>Reactivity</b>	No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	Oxidizers
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
<b>Hazardous polymerization</b>	Under normal conditions of storage and use, hazardous polymerization will not occur.

## Section 11. Toxicological information

<b>Information on toxicological effects</b>	
<b>Acute toxicity</b>	Not available.
<b>Irritation/Corrosion</b>	Not available.
<b>Sensitization</b>	Not available.
<b>Mutagenicity</b>	Not available.
<b>Carcinogenicity</b>	Not available.



### Classification

Product/ingredient name	OSHA	IARC	NTP
Methyl Fluoride	-	3	-

**Reproductive toxicity** Not available.

**Teratogenicity** Not available.

**Specific target organ toxicity (single exposure)** Not available.

**Specific target organ toxicity (repeated exposure)** Not available.

**Aspiration hazard** Not available.

**Information on the likely routes of exposure** Not available.

**Potential acute health effects**

**Eye contact** Contact with rapidly expanding gas may cause burns or frostbite.

**Inhalation** No known significant effects or critical hazards.

**Skin contact** Contact with rapidly expanding gas may cause burns or frostbite.

**Ingestion** As this product is a gas, refer to the inhalation section.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact** No specific data.

**Inhalation** No specific data.

**Skin contact** No specific data.

**Ingestion** No specific data.

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

**Potential immediate effects** Not available.

**Potential delayed effects** Not available.

**Long term exposure** Not available.

**Potential immediate effects** Not available.

**Potential delayed effects** Not available.

**General** No known significant effects or critical hazards.

**Carcinogenicity** No known significant effects or critical hazards.

**Mutagenicity** No known significant effects or critical hazards.

**Teratogenicity** No known significant effects or critical hazards.

**Developmental effects** No known significant effects or critical hazards.

**Fertility effects** No known significant effects or critical hazards.

**Numerical measures of toxicity** Not available.

**Acute toxicity estimates**



### Section 12. Ecological information

**Toxicity** Not available.

**Persistence and degradability** Not available.

**Bioaccumulative potential** Not available.

Product/ingredient name	LogPow	BCF	Potential
Methyl Fluoride	0.51	-	low

**Mobility in soil** Not available.

**Soil/water partition coefficient (KOC)** Not available.






**Other adverse effects** No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty Airgas-owned pressure vessels should be returned to Airgas. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

### Section 14. Transport information

	DOT	TDG	Mexico	IMDG	IATA
<b>UN number</b>	UN2454	UN2454	UN2454	UN2454	UN2454
<b>UN proper shipping name</b>	METHYL FLUORIDE, OR REFRIGERANT GAS R 41	METHYL FLUORIDE, OR REFRIGERANT GAS R 41	METHYL FLUORIDE, OR REFRIGERANT GAS R 41	METHYL FLUORIDE, OR REFRIGERANT GAS R 41	METHYL FLUORIDE, OR REFRIGERANT GAS R 41

Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

“Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product.”

### Additional information

#### DOT Classification

Limited quantity Yes.

Quantity limitation Passenger aircraft/rail: Forbidden. Cargo aircraft: 150 kg.

#### TDG Classification

Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).

Explosive Limit and Limited Quantity Index 0.125

ERAP Index 3000

Passenger Carrying Ship Index Forbidden

Passenger Carrying Road or Rail Index Forbidden

#### IATA

Quantity limitation Passenger and Cargo Aircraft: Forbidden. Cargo Aircraft Only: 150 kg.

#### Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### Transport in bulk according to IMO instruments

Not available.

## Section 15. Regulatory information

#### U.S. Federal regulations Clean Air Act Section 112

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Not listed

#### (b) Hazardous Air Pollutants (HAPs)

#### Clean Air Act Section

Not listed

#### 602 Class I Substances

#### Clean Air Act Section

Not listed

#### 602 Class II Substances

#### DEA List I Chemicals

Not listed

### (Precursor Chemicals)

**DEA List II Chemicals** Not listed

### (Essential Chemicals)

**SARA 302/304** No products were found.

### Composition/information on ingredients

**SARA 304 RQ** 10 lbs / 4.5 kg

**SARA 311/312** Refer to Section 2: Hazards Identification of this SDS for classification of substance.

### Classification

### State regulations

**Massachusetts** This material is listed.

**New York** This material is listed.

**New Jersey** This material is listed.

**Pennsylvania** This material is listed.

### International regulations

**Chemical Weapon** Not listed.

### Convention List

### Schedules I, II & III

### Chemicals

**Montreal Protocol** Not listed.

**Stockholm Convention** Not listed.

### on Persistent Organic

### Pollutants

**Rotterdam Convention** Not listed.

### on Prior Informed

### Consent (PIC)

**UNECE Aarhus Protocol** Not listed.

### on POPs and Heavy

### Metals

### Inventory list

**Australia** Not determined.

**Canada** This material is not listed in DSL but is listed in NDSL.

**China** This material is listed or exempted.

**Europe** This material is listed or exempted.

**Japan** Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): This material is listed or exempted.

**New Zealand** This material is listed or exempted.

**Philippines** This material is listed or exempted.

**Republic of Korea** This material is listed or exempted.

**Taiwan** This material is listed or exempted.

**Thailand** Not determined.

**Turkey** Not determined.

**United States** This material is listed or exempted.

Viet Nam

Not determined.

## Section 16. Hazards identification

### Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		4
Physical hazards		3

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)

Health 2		Flammability 4
		Instability/Reactivity 0
		Special

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE GASES - Category 1	Expert judgment
GASES UNDER PRESSURE - Compressed gas	According to package

### History

Date of printing	2023/01/01
Date of issue/Date of	2023/01/01

Date of issue/Date of revision: 2023/01/01

Date of previous issue: 2023/01/01

### revision

**Date of previous issue** 2023/01/01

**Version** 1

**Key to abbreviations**

ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 UN = United Nations

**References** Not available

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.